DATA COLLECTORS

• Product availability and specifications depend on territoty market strategy; all are subjects to change without prior notice.

▼ℤΕΒΕΥ is the trademark of ℤΕΒΕΧ INDUSTRIES INC., all rights reserved.



B1F-1, 207 Besin Rd, Sec. 3 Sindian City, Taipei, Taiwan T. +886-2-8913 2598 F. +886-2-8913 2596 E. mail@zebex.com W. www.zebex.com

Z-2050 Series

Proprietary Handheld Terminal

The Z-2050 Series is a combination of high performance and low power consumption handheld terminal. Its proprietary operating system gives integrator maximum productivity in inventory, stock and asset management with flexibility and efficiency anytime anywhere.

- Own-design GUI operating system
- Sophisticated function at option
- Fasy to read, backlit I CD screen with touch panel.

• Easy to read, backlit LCD screen with touch panel		
MODELS Engine Type	Z-2050BA 1D laser engine	Z-2052BA 2D image engine
CPU Operating System RAM F-ROM Display Keypads & Buttons Interfaces	MOTOROLA 33MHz processor Own-design GUI operating system 8MB 4MB core flash memory and 64MB data flash memory 2.5" FSTN, 160 × 160 dots graphic LCD with touch panel and back light Total 30 keys for alpha/numeric input and system control RS232, USB 1.1 Client, IrDA 1.1	
POWER Main Battery Backup Battery Battery Life	2,200 mAH, 3.7V, Li-Ion rechargeable battery 45 mAH, 3.0V, Lithium rechargeable battery 16 hours	
PHYSICAL Dimensions Weight	$190.0 \times 74.9 \times 46.5$ mm Approx. 330 g (battery included)	
ENVIRONMENTAL Operating Temperature Storage Temperature Operating Humidity Storage Humidity Drop Durability Environmental Sealing	0°C - 50°C (32°F - 122°F) -10°C - 60°C (14°F - 140°F) 10% - 70% RH (non-condensing) 5% - 70% RH (non-condensing) Withstand 1.2M drop onto concrete IP54 rated sealing	
REGULATORY EMC	CE & FCC Part 15B, 15C	
SOFTWARE & DEVELOPMENT	(a) Microsoft VC++ 6.0 development environment; (b) Supports GUI, database and over 1,000 API	





















