

HANDHELD SCANNERS

ZEBEX
ZEBEX INDUSTRIES INC.

B1F-1, 207, Sec. 3 Beisun Rd.
Sindian City, Taipei, Taiwan

T. +886-2-8913 2598

F. +886-2-8913 2596

E. mail@zebex.com

W. www.zebex.com

* Product availability and specifications depend on territory market strategy; all are subjects to change without prior notice.
* ZEBEX is the trademark of ZEBEX INDUSTRIES INC., all rights reserved.

Z-3050BT

Wireless Handheld CCD Scanner

Featured with ZEBEX proprietary hardware decoding technology, the Z-3050BT secures accurate and sensitive scanning performance.

- Wireless freedom
- Data connection flexibilities
- Flashing LED indication and programmable beeper
- Smart charging to prolong battery life
- Light-weighted and streamlined shape for easy handy operation

OPERATIONAL	
Light Source	617 nm visible LED
Optical System	Linear CCD array
Depth of Field	10 – 200 mm (UPC/EAN 100%, PCS=90%)
Width of Field	180 mm @ 200 mm of depth
Scan Rate	100 scans per second
Minimum Bar Width	5 mil @ PCS=90%
Print Contrast	30% @ UPC/EAN 100%
Indicators (LED)	Three-color LED (green, red & blue)
Beeper Operation	Programmable tone & beep time
System Interfaces	Keyboard, RS-232C, HID USB, wand
PHYSICAL	
Dimensions	106.7 × 58.0 × 155.0 mm (device only)
Weight	200 g (stand excluded); 563 g (stand included)
Cable	Standard 2M straight
POWER	
Input Voltage	9V DC 1A at charging
Battery	2 AA NiMH rechargeable batteries
Operating Autonomy	Over 24,000 reads at full charged by scanning once per 10 seconds
Recharge Time	5 hours (max.)
RADIO COMMUNICATION	
Protocol	Serial Protocol Profile (SPP)
Radio Frequency	2.4 – 2.48 GHz
Working Range	Up to 100M / 75M (depends on operating environment)
REGULATORY	
EMC	CE & FCC DOC compliance
Radio	FCC TCB, EN 300 328, ARIB STD-T66
ENVIRONMENTAL	
Operating Temperature	0°C – 40°C (32°F – 104°F)
Storage Temperature	-20°C – 60°C (-4°F – 140°F)
Humidity	5% – 95% RH (non-condensing)
Light Levels	4,500 Lux (fluorescence)
Drop Durability	Designed to withstand 1M drops

