


[Buyer's Guide]



Z-5151 Series High-Speed Laser Scan Module

Standard Version

Standard Device



PIN-OUT CONFIGURATION			
1	+5V	2	RTS
3	CTS	4	TX
5	RX	6	KB_DATA
7	PC_CLK		READ_OUT
8	PC_DATA	9	KB_CLK
10	GND		TRIGGER

Barcode	P/N	Model No.	Remark
	88M-5100KP-001	Z-5151(K)	Standard device w/PS/2 cable
	88M-5100RP-001	Z-5151(R)	Standard device w/RS232 cable (DTE pin-out)
	88M-5100ML-001	Z-5151(R)	Standard device w/RS-232 cable (Multi-Interface w/o Connector)
	88M-5100UB-001	Z-5151(U)	Standard device w/USB cable

Standard Cable Options

- The standard cable is black, straight, and 2 meters (6.5 feet) in length.
- The standard cable options include keyboard wedge, RS-232 and USB.
- Special Order Requirement:
ZEBEX is capable of supplying special customized cables, given that customers provide detailed pin configurations. Please contact your sales representative to further discuss the minimum order quantity of the special cables.

1. Keyboard wedge connection for PS/2 compatible terminal

PIN-OUT CONFIGURATION			
MINI DIN (M)		MINI DIN(F)	
DIN	FUNATION	DIN	FUNATION
1	PC Data	1	KB Data
2	N.C.	2	N.C.
3	GND	3	GND
4	+5V	4	+5V
5	PC Clock	5	KB Clock
6	N.C.	6	N.C.

Item Part No: 170-50K010-200



