


Z-8062 2D Image Hands-Free Scanner

Standard Device



Ordering Information


Barcode	P/N	Model Name	Remark
	88F-6200UB-000	Z-8062(U)	2D Image Hands-Free Scanner USB
	88F-6200RP-A00	Z-8062(R)	2D Image Hands-Free Scanner RS232 AU adapter
	88F-6200RP-E00	Z-8062(R)	2D Image Hands-Free Scanner RS232 EU adapter
	88F-6200RP-K00	Z-8062(R)	2D Image Hands-Free Scanner RS232 UK adapter
	88F-6200RP-U00	Z-8062(R)	2D Image Hands-Free Scanner RS232 US adapter

[Buyer's Guide]

Standard Cable Options

- The standard cable is black, straight, and 2 meters (6.5 feet) in length unless specified otherwise in notes.
- The standard cable options include RS-45 10P10C, RS-232, USB, and etc.
- Special Order Requirement:
ZEBEX is capable of supplying special customized cables, given that customers provide detailed pin configurations. Please contact your sales representative to further discuss the minimum order quantity of the special cables.

1. RS-232 interface (DTE Pinout) – Power adapter required if host can not provide sufficient power




PIN-OUT CONFIGURATION			
PIN	FUNCTION	PIN	FUNCTION
1	N.C.	6	N.C.
2	TXD	7	CTS
3	RXD	8	RTS
4	N.C.	9	+5V Input
5	GND		

Inner of DC-Jack: +5V DC
Outer of DC-Jack: GND

Cable Part Number: 170-21R4Z8-210



2. USB /USB virtual COM interface



PIN	FUNCTION
1	VBUS
2	D-
3	D+
4	GND


Cable Part Number: 170-20UC38-211



* Additional software or special firmware may be required for activating virtual COM interface.

Power Adapter

The device requires a minimum of 250mA at 5 VDC power and consumes power from the host machine. If the host can not supply sufficient power, ZEBEX provides adapters of the following plug types:



* The figures are for reference only. The adaptor form factor is subject to change without prior notice.