## HANDS-FREE SCANNER





**2D Image Hands-Free Scanner** (Preliminary)





The Z-8072 Plus 2D Image Hands-Free Scanner provides great features with enhanced performance.

The powerful 2D Scanner and the compact size allow users to aim intuitively with accuracy even if space is limited. Furthermore, it is designed to read barcodes off smart phone screens even when they are in low backlight settings. It is the perfect solution for any space-constrained environments.

- Enhanced to quickly scan barcode at low-brightness on smart phone screen
- · Enhanced scanning on reflective surfaces
- · Enhanced scanning sensitivity, range, and speed
- · Enhanced readability in special environments
- · Easy to use; setting change not necessary for different applications

1. Distinctive indicator

- 2. Large button & slip proof design
- 3.45° tilting angles



• Product availability and specifications depend on territory market strategy; all are subjects to change without prior notice. • ZZEBEX is the trademark of ZEBEX INDUSTRIES INC, all rights reserved.

## **ZEBEX INDUSTRIES INC.**

B1F.-1, No. 207, Sec. 3, Beixin Rd, Xindian Dist, New Taipei City 23143, Taiwan

Aiming Element	617 nm LED
Illumination Element	617 nm LED
Optical System	752H×480V pixels (WVGA)
Scan Angle	44.4° horizontal; 29.1° vertical
Depth of Field	Code39 (5 mil): 0 – 50 mm EAN13 (13 mil): 0 – 210 mm (Note: DOF may vary depending on environment condition and barcode quality
Min. Bar Width	6.8 mil (PDF 417), 5 mil (Code 39)
Print Contrast	30% @ UPC/EAN 100%
Indicator	Color LED
Programmabl Operation	Scan Mode, Beeper tone
System Interface	RS-232, USB
PHYSICAL	
Dimension	145.0 × 97.0 × 80.0 mm
Weight	250 g
POWER	
Input Voltage	5 VDC ±10%
Operating Current	400 mA typical
REGULATORY	
EMC	CE, FCC, VCCI, BSMI
Safety	IEC 62471 Exempt
ENVIRONMENTAL	
Operating Temperature	0°C – 50°C (32°F – 122°F)
Storage Temperature	-40°C – 70°C (-40°F – 158°F)
Humidity	5% – 95% RH (non-condensing)
Light level	Max. 100,000 Lux
Drop Durability	Designed to withstand 1M drops
<b>DECODING CAPABIL</b>	ITY
1D Barcode	UPC/EAN [UPCA/UPCE/ EAN-8/ EAN-13, ISBN (Bookland), ISSN], Code 39 (Standard, Full ASCII, Trioptic, Code 32 (Italian Pharmacode), Code 128, Code 93, Codabar, 2 of 5 (Interleaved 2 of 5, Discrete 2 of 5, IATA, Matrix 2 of 5, Code11), MSI Plessey GS1 DataBar (Omnidirectional, Truncated, Stacked, Stacked Omnidirectional, Limited, Expanded, Expanded Stacked)
2D Barcode	PDF417, MicroPDF417, Composite Codes (CC-A, CC-B, CC-C), Aztec (Standard, Inverse), Maxicode, Data Matrix/ ECC 200 (Standard, Inverse), QR Code (Standard, Inverse, Micro)

ZEBEX



**1**+886-2-8913 2598 **G** +886-2-8913 2596

E mail@zebex.com Www.zebex.com