



## Z-900xBT Series

**2015 NEW**

### Portable Data Collector



Z-900xBT Series redefines simplicity with more simple features and less complicated options. With wireless connectivity, users can transfer data instantly allowing seamless, real-time reporting and inventory control. Enhanced with the brand-new, easy-to-use ZEBEX Application Creator program, Z-900xBT Series allows users to achieve maximum efficiency through intuitive settings and user friendly interfaces. In addition, Z-900xBT Series is uniquely shaped with a neat and rugged appearance to allow precision control with just one hand. Optimized to fit your needs, the Z-900xBT Series comes with wide variety of scanning options, including 1D, 2D, and laser readers.

- Simple, easy to understand interface
- Transflective LCD for a wide working condition
- No programming background required
- Wireless connectivity
- Compatible with Windows PC

1. Compact and ergonomic design
2. Easy to use cradle
3. Antimicrobial housing available for medical usage



- Product availability and specifications depend on territory market strategy; all are subjects to change without prior notice.
- ZEBEX is the trademark of ZEBEX INDUSTRIES INC, all rights reserved.

MODEL	Z-9000BT	Z-9001BT	Z-9002BT
Input Device	1D CCD scan engine	1D laser scan engine	2D image reader
SYSTEM			
CPU	32-bit RISC ARM Cortex-M4 100MHz microprocessor		
Memory	8MB flash ROM & 4MB RAM (8MB optional)		
Display	Mono FSTN, 128 × 128 dots graphic LCD with white back light		
Keypad & Button	Total 21 keys for full alpha/numeric input and system control keypads with LED back light		
Indicator	Two-color LED (green & red)		
Beeper Operation	Programmable tone & beep time		
Interface	USB 2.0 full-speed device compliant		
RADIO COMMUNICATION			
Wireless	RF wireless compatible with SPP profile mode		
Working Range	Up to 80M (depends on operating environment)		
POWER			
Main Battery	1,150 mAh, 3.7V Li-ion rechargeable battery		
Backup Battery	15 mAh, 3.0V Lithium rechargeable battery		
PHYSICAL			
Dimension	132.0 × 59.0 × 29.0 mm		
Weight	160 g (battery included)		
ENVIRONMENTAL			
Operating Temperature	0°C – 50°C (32°F – 122°F)		
Storage Temperature	-20°C – 60°C (-4°F – 140°F)		
Humidity	5% – 95% RH (non-condensing)		
Drop Durability	Designed to withstand 1.2M drops		
Tumble Resistance	0.5M × 1000 times		
Environmental Sealing	IP54 rated sealing		
REGULATORY			
Safety	FCC, CE, BSMI		
Radio	FCC Part 15C; CE EN 300 328; NCC (Taiwan)		
ACCESSORY			
Standard	Batch cradle, Li-ion battery, USB cable, power adapter, hand strap		
SOFTWARE & DEVELOPMENT	(a) Support the ZAC (ZEBEX Application Creator); (b) SDK to support C-Language compatible compiler		



**ZEBEX INDUSTRIES INC.**

**A** B1F.-1, No. 207, Sec. 3, Beixin Rd, Xindian Dist, New Taipei City 23143, Taiwan

**T** +886-2-8913 2598

**F** +886-2-8913 2596

**E** mail@zebex.com

**W** www.zebex.com

Ver. 20150701